

硬銅絞線及軟銅絞線



Anneal & Hard-draw Copper stranded Conductor

CNS 668/1365

公稱 截面積 normal cross-section area	線數/線徑 no./mm	絞合 外徑 stranding Overall Diameter	重量 weight Kg/km	最大導體電阻 (20°C)max. conductor-resistance		硬銅線 最小拉力 hard draw Min. Load	標準 長度 length m
				硬銅線	軟銅線		
				Hard-draw	Anneal		
mm ²	no./mm	mm	Kg/km	Ω/km	Ω/km	kgf	m
1000	127/3.2	41.6	9315	0.0179	0.0175	40060	300
850	127/2.9	37.7	7651	0.0217	0.0213	33150	300
725	91/3.2	35.2	6655	0.0248	0.0243	28710	300
600	91/2.9	31.9	5466	0.0303	0.0296	23750	300
500	61/3.2	28.8	4448	0.0370	0.0362	19240	300
400	61/2.9	26.1	3654	0.0450	0.0448	15920	300
325	61/2.6	23.4	2937	0.0560	0.0548	12900	300
250	61/2.3	20.7	2298	0.0715	0.0701	10170	300
200	37/2.6	18.2	1776	0.0920	0.0902	7820	500
150	37/2.3	16.1	1390	0.118	0.115	6160	600
125	19/2.9	14.5	1129	0.143	0.140	4950	600
100	19/2.6	13.0	907.6	0.178	0.175	4010	600
80	19/2.3	11.5	710.3	0.228	0.223	3160	1000
60	19/2.0	10.0	537.0	0.301	0.295	2410	1000
50	19/1.8	9.0	435.1	0.376	0.368	1960	1000
38	7/2.6	7.8	334.4	0.484	0.474	1480	300
30	7/2.3	6.9	261.7	0.618	0.606	1160	300
22	7/2.0	6.0	197.9	0.818	0.801	889	300
14	7/1.6	4.8	126.7	1.29	1.26	574	500
8	7/1.2	3.6	71.19	2.30	2.25	326	500
5.5	7/1.0	3.0	49.46	3.31	3.24	228	500
3.5	7/0.8	2.4	31.66	5.17	5.06	146	500
2	7/0.6	1.8	17.80	9.18	9.00	82	500
1.4	7/0.5	1.5	12.37	13.2	12.95	57	500
1.25	7/0.45	1.35	10.02	16.29	16.16	46	500
0.9	7/0.4	1.2	7.913	20.7	20.41	36	500



大亞電線電纜股份有限公司



總公司: 台南縣關廟鄉71847中山路二段249號

TEL: 06-5953131

FAX: 06-5958190

台北分公司: 台北縣24886五股工業區五工路149號7樓

TEL: 02-22997070

FAX: 02-22997123

網址: www.taya.com.tw