

15KV XLPE低煙無毒電纜

參照中國國家標準CNS

低  
煙  
無  
毒  
電  
纜

	公稱斷面積	最小平均絕緣厚度	最小平均被覆厚度	約計完成外徑	試驗電壓	20°C最大導體電阻	20°C最小絕緣電阻	約計重量	標準單長
	mm <sup>2</sup>	mm	mm	mm	KV/5分	Ω/km	MΩ-km	kg/km	m
中性點 接地系統 單心	38	4.45	2.03	25	35	0.487	3,500	885	300
	60	4.45	2.03	27	35	0.303	3,000	1,145	300
	100	4.45	2.03	29	35	0.180	2,500	1,595	200
	150	4.45	2.03	33	35	0.118	2,000	2,220	200
	200	4.45	2.03	35	35	0.0922	2,000	2,680	200
	250	4.45	2.03	37	35	0.0722	1,500	3,220	200
	325	4.45	2.03	40	35	0.0565	1,500	3,950	200
	400	4.45	2.03	43	35	0.0454	1,500	4,730	150
中性點 接地系統 三心	38	4.45	2.79	49	35	0.497	3,500	2,630	200
	60	4.45	2.79	53	35	0.309	3,000	3,410	200
	100	4.45	2.79	59	35	0.184	2,500	4,770	150
	150	4.45	2.79	67	35	0.120	2,000	6,615	150
	200	4.45	2.79	71	35	0.0940	2,000	8,020	150
	250	4.45	3.58	78	35	0.0736	1,500	9,650	150
	325	4.45	3.58	84	35	0.0576	1,500	11,800	150
中性點非 接地系統 單心	38	5.59	2.03	27	44	0.487	3,500	980	200
	60	5.59	2.03	29	44	0.303	3,000	1,245	200
	100	5.59	2.03	32	44	0.180	2,500	1,705	150
	150	5.59	2.03	35	44	0.118	2,500	2,345	150
	200	5.59	2.03	37	44	0.0922	2,000	2,810	150
	250	5.59	2.03	39	44	0.0722	2,000	3,355	150
	325	5.59	2.79	44	44	0.0565	2,000	4,260	150
	400	5.59	2.79	47	44	0.0454	1,500	5,060	150
中性點非 接地系統 三心	38	5.59	2.79	54	44	0.497	3,500	2,930	150
	60	5.59	2.79	58	44	0.309	3,000	3,735	150
	100	5.59	2.79	64	44	0.184	2,500	5,125	150
	150	5.59	2.79	72	44	0.120	2,500	7,050	150
	200	5.59	3.58	76	44	0.0940	2,000	8,450	150
	250	5.59	3.58	82	44	0.0736	2,000	10,390	150
325	5.59	3.58	89	44	0.0576	2,000	12,670	150	

