

25KV XLPE低煙無毒電纜

參照中國國家標準CNS

低  
煙  
無  
毒  
電  
纜

	公稱斷面積	最小平均絕緣厚度	最小平均被覆厚度	約計完成外徑	試驗電壓	20°C最大導體電阻	20°C最小絕緣電阻	約計重量	標準單長
	mm <sup>2</sup>	mm	mm	mm	KV/5分	Ω/km	MΩ-km	kg/km	m
中性點 接地系統 單心	38	6.6	2.03	30	52	0.487	3,600	1,100	300
	60	6.6	2.03	32	52	0.393	3,000	1,360	300
	100	6.6	2.03	35	52	0.180	2,800	1,870	200
	150	6.6	2.03	39	52	0.118	2,000	2,470	200
	200	6.6	2.03	40	52	0.0922	2,000	2,950	200
	250	6.6	2.03	43	52	0.0722	1,800	3,500	200
	325	6.6	2.79	48	52	0.0565	1,500	4,420	200
	400	6.6	2.79	51	52	0.0454	1,500	5,270	150
	500	6.6	2.79	53	52	0.0373	1,500	6,200	150
中性點 接地系統 三心	38	6.6	2.79	60	52	0.497	3,600	3,250	200
	60	6.6	2.79	64	52	0.309	3,000	4,050	200
	100	6.6	2.79	71	52	0.184	2,800	5,600	150
	150	6.6	3.58	79	52	0.120	2,000	7,650	150
	200	6.6	3.58	83	52	0.0940	2,000	9,100	150
	250	6.6	3.58	88	52	0.0736	1,800	10,800	150
	325	6.6	3.58	95	52	0.0576	1,500	13,100	150
中性點非 接地系統 單心	38	8.76	2.03	35	64	0.487	4,500	1,380	200
	60	8.76	2.03	37	64	0.309	3,800	1,660	200
	100	8.76	2.03	40	64	0.180	3,500	2,150	150
	150	8.76	2.03	43	64	0.118	3,200	2,760	150
	200	8.76	2.79	47	64	0.0922	2,800	3,410	150
	250	8.76	2.79	50	64	0.0722	2,800	4,050	150
	325	8.76	2.79	53	64	0.0565	2,400	4,850	150
	400	8.76	2.79	55	64	0.0454	2,000	5,600	150
	500	8.76	2.79	58	64	0.0373	2,000	6,600	150
中性點非 接地系統 三心	38	8.76	2.79	71	64	0.497	4,500	4,100	150
	60	8.76	3.58	77	64	0.309	3,800	5,200	150
	100	8.76	3.58	82	64	0.184	3,500	6,700	150
	150	8.76	3.58	89	64	0.120	3,200	8,600	150
	200	8.76	3.58	93	64	0.0940	2,800	10,100	150
	250	8.76	3.58	99	64	0.0736	2,800	12,050	150
	325	8.76	3.58	106	64	0.0576	2,400	14,350	150

註：除單心及三心電纜外，本公司尚供應單心三股絞電纜。

