

600V 380°C 耐熱電纜



- 規格：內政部消防署耐熱電線電纜認可基準
- 用途：室內外消防設備，火災警報系統，緊急用電系統，廣播系統，通信系統
- 構造：導體- 圓形或圓形壓縮軟銅絞線
絕緣- 交連聚乙烯(XLPE)
識別- 單芯：自然色
多芯：以適當方式識別
包帶- 僅多芯需要
被覆- 聚氯乙烯(PVC)或低煙無毒(LSHF)

導體			芯數/對數	完成外徑 mm	最大 導體電阻 (20°C) Ω/km	最小 絕緣電阻 MQ-km		試驗電壓 kV							
標稱 截面積 mm/mm ²	構成 No./mm	外徑 (約) mm				20°C	75°C								
1.2mm ²	1/1.2	1.2	1C	3.8	16.0	50	0.05	1.5							
			2C	5.9											
			3C	6.3											
			4C	6.8											
			5C	7.3											
			6C	7.9											
			8C	8.6											
			10C	9.9											
			2P	8.6											
			3P	9.5											
			4P	10.5											
			5P	11.4											
			10P	15.7											
			15P	18.3											
			20P	21.2											
			1.6mm ²	1/1.6					1.6	1C	4.3	9.01	50	0.05	1.5
2C	6.9														
3C	7.3														
4C	8.0														
5C	8.7														
6C	9.4														
8C	10.2														
10C	11.9														
2P	10.2														
3P	11.3														
4P	12.6														
5P	13.8														
10P	19.4														
15P	22.6														
20P	26.3														
2.0mm ²	1/2.0	2.0			1C	4.7	5.77	50		0.05	1.5				
			2C	7.7											
			3C	8.2											
			4C	9.0											
			5C	9.8											
			6C	10.6											
			8C	11.5											
			10C	13.5											
			2P	11.6											
			3P	12.8											
			4P	14.3											
			5P	15.7											
			10P	22.4											
			15P	26.0											
			1.25mm ²	7/0.45	1.35	1C			4.1			16.8	50	0.05	1.5
						2C			6.4						
3C	6.8														
4C	7.4														
5C	8.0														
6C	8.7														
8C	9.4														
10C	10.9														
2P	9.4														
3P	10.4														
4P	11.5														
5P	12.6														
10P	17.6														
15P	20.4														
20P	23.7														

導體			芯數/對數	完成外徑 mm	最大 導體電阻 (20°C) Ω/km	最小 絕緣電阻 MQ-km		試驗電壓 kV							
標稱 截面積 mm/mm ²	構成 No./mm	外徑 (約) mm				20°C	75°C								
2mm ²	7/0.6	1.8	1C	4.5	9.43	50	0.05	1.5							
			2C	7.3											
			3C	7.8											
			4C	8.5											
			5C	9.2											
			6C	10.0											
			8C	10.9											
			10C	12.7											
			2P	10.9											
			3P	12.1											
			4P	13.5											
			5P	14.8											
			10P	21.0											
			15P	24.4											
			20P	28.1											
			3.5mm ²	7/0.8					2.4	1C	5.1	5.20	50	0.05	1.5
2C	8.5														
3C	9.1														
4C	9.9														
5C	10.9														
6C	11.8														
8C	12.9														
10C	15.1														
5.5mm ²	7/1.0	3.0			1C	5.8	3.33	50		0.05	1.5				
					2C	9.9									
			3C	10.6											
			4C	11.6											
			5C	12.7											
			6C	13.9											
			8C	14.3											
			10C	18.0											
			8mm ²	7/1.2	3.6	1C			6.4			2.31	50	0.05	1.5
						2C			11.1						
3C	11.9														
4C	13.1														
5C	14.4														
6C	15.7														
8C	17.3														
10C	20.5														

* 上述各規格中 2C 與 1P 之結構尺寸相同。

* 版權屬於華新麗華股份有限公司所有，非經授權不得擅自修改或複製。



總公司：台北市信義區松智路 1 號 25 樓
新莊廠：台北縣新莊市新樹路 397 號

TEL：(02) 87262211
業務專線_TEL：(02) 22029121
(02) 22025155

FAX：(02) 27202234
FAX：(02) 22025166