

耐熱電纜構造表

▶ 耐熱電纜構造表

圓型電纜

導體尺寸	心數	絕緣厚度	被覆厚度	約計完成外徑	最大導體電阻 (20℃)	試驗電壓	最小絕緣電阻 (20℃)	標準單長
mm	C	mm	mm	mm	Ω/Km	V/1min	MΩKm	m
1.2	1	0.4	0.8	4.1	16.0	1500	50	300
1.2	2	0.4	0.9	6.5	16.0	1500	50	300
1.2	3	0.4	0.9	6.9	16.0	1500	50	300
1.2	4	0.4	0.9	7.4	16.0	1500	50	300
1.2	5	0.4	0.9	7.9	16.0	1500	50	300
1.2	6	0.4	0.9	8.8	16.0	1500	50	300
1.2	7	0.4	0.9	8.8	16.0	1500	50	300
1.6	1	0.4	0.8	4.5	9.01	1500	50	300
1.6	2	0.4	0.9	7.2	9.01	1500	50	300
1.6	3	0.4	0.9	7.6	9.01	1500	50	300
1.6	4	0.4	0.9	8.5	9.01	1500	50	300
1.6	5	0.4	0.9	9.0	9.01	1500	50	300
1.6	6	0.4	0.9	9.8	9.01	1500	50	300
1.6	7	0.4	0.9	9.8	9.01	1500	50	300
2.0	1	0.4	0.8	5.0	5.77	1500	50	300
2.0	2	0.4	0.9	8.0	5.77	1500	50	300
2.0	3	0.4	0.9	8.5	5.77	1500	50	300
2.0	4	0.4	0.9	9.3	5.77	1500	50	300
2.0	5	0.4	0.9	10.1	5.77	1500	50	300
2.0	6	0.4	0.9	10.9	5.77	1500	50	300
2.0	7	0.4	0.9	10.9	5.77	1500	50	300