

XLPE-PVC 電力電纜



- 規格：CNS 2655
 - 用途：輸配電系統
 - 額定：0-25000 V
 - 構造：導體- 圓形或圓形壓縮軟銅絞線
 - *導體遮蔽- 半導電層
 - 絕緣- 交連 PE
 - 識別- 單芯：自然色
 - 多芯：適當方式識別
 - *絕緣遮蔽- 半導電層
 - *遮蔽- 軟銅帶
 - 被覆- 黑色 PVC
- *註：2001 V 以上須加導體遮蔽、絕緣遮蔽及遮蔽銅帶。

| | 導體 | | | 絕緣厚度 | 被覆厚度 | 最大 導體電阻 (20℃) | 試驗電壓 kV | 最小 絕緣電阻 (20℃) MΩ-km | 完成外徑 (約) mm |
|------------|-----------------|-------|-----------|--------|------|---------------------|------------|------------------------------|-------------------|
| | 標稱 截面 | 構成 | 外徑 (約) | | | | | | |
| | mm ² | No/mm | mm | | | | | | |
| 600V 單芯 | 2.0 | 1/1.6 | 1.6 | 0.76 | 0.38 | 8.92 | 3.5 | 2500 | 4.2 |
| | | 1/2.0 | 2.0 | 0.76 | 0.38 | 5.65 | 3.5 | 2000 | 4.3 |
| | | 1/2.6 | 2.6 | 0.76 | 0.38 | 3.35 | 3.5 | 2000 | 4.9 |
| | | 1/3.2 | 3.2 | 1.14 | 0.38 | 2.21 | 5.5 | 2000 | 6.7 |
| | | 7/0.6 | 1.8 | 0.76 | 0.38 | 9.24 | 3.5 | 2500 | 4.4 |
| | | 7/0.8 | 2.4 | 0.76 | 0.38 | 5.20 | 3.5 | 2000 | 5.0 |
| | | 7/1.0 | 3.0 | 0.76 | 0.38 | 3.33 | 3.5 | 2000 | 5.6 |
| | | 8 | 7/1.2 | 3.6 | 1.14 | 0.38 | 2.31 | 5.5 | 1500 |
| | 圓形 壓縮 | 14 | 4.4 | 1.14 | 0.76 | 1.30 | 5.5 | 1500 | 8.7 |
| | | 22 | 5.5 | 1.14 | 0.76 | 0.824 | 5.5 | 1500 | 9.8 |
| | | 30 | 6.3 | 1.40 | 0.76 | 0.623 | 7.0 | 1500 | 11.1 |
| | | 38 | 7.1 | 1.40 | 0.76 | 0.487 | 7.0 | 1000 | 11.9 |
| | | 50 | 8.2 | 1.40 | 1.14 | 0.378 | 7.0 | 1000 | 13.7 |
| | | 60 | 9.1 | 1.40 | 1.14 | 0.303 | 7.0 | 1000 | 14.6 |
| | | 80 | 10.5 | 1.40 | 1.14 | 0.229 | 7.0 | 1000 | 16.0 |
| | | 100 | 11.9 | 1.40 | 1.14 | 0.180 | 7.0 | 800 | 17.4 |
| | | 125 | 13.2 | 1.65 | 1.14 | 0.144 | 8.0 | 800 | 19.2 |
| | | 150 | 14.7 | 1.65 | 1.65 | 0.118 | 8.0 | 800 | 21.7 |
| | | 200 | 16.6 | 1.65 | 1.65 | 0.0922 | 8.0 | 800 | 23.6 |
| | | 250 | 18.9 | 1.65 | 1.65 | 0.0722 | 8.0 | 600 | 25.9 |
| 325 | 21.3 | 2.03 | 1.65 | 0.0565 | 10.0 | 600 | 29.1 | | |
| 400 | 24.1 | 2.03 | 1.65 | 0.0454 | 10.0 | 600 | 32.0 | | |
| 500 | 26.9 | 2.03 | 1.65 | 0.0373 | 10.0 | 600 | 34.5 | | |
| 600V 二芯 | 2.0 | 1/1.6 | 1.6 | 0.76 | 1.14 | 9.10 | 3.5 | 2500 | 9.4 |
| | | 1/2.0 | 2.0 | 0.76 | 1.14 | 5.76 | 3.5 | 2000 | 10.2 |
| | | 1/2.6 | 2.6 | 0.76 | 1.14 | 3.42 | 3.5 | 2000 | 11.4 |
| | | 1/3.2 | 3.2 | 1.14 | 1.14 | 2.25 | 5.5 | 2000 | 14.4 |
| | | 7/0.6 | 1.8 | 0.76 | 1.14 | 9.42 | 3.5 | 2500 | 9.8 |
| | | 7/0.8 | 2.4 | 0.76 | 1.14 | 5.30 | 3.5 | 2000 | 11.0 |
| | | 7/1.0 | 3.0 | 0.76 | 1.14 | 3.40 | 3.5 | 2000 | 12.2 |
| | | 8 | 7/1.2 | 3.6 | 1.14 | 2.36 | 5.5 | 1500 | 16.0 |
| | 圓形 壓縮 | 14 | 4.4 | 1.14 | 1.52 | 1.33 | 5.5 | 1500 | 17.2 |
| | | 22 | 5.5 | 1.14 | 1.52 | 0.840 | 5.5 | 1500 | 19.5 |
| | | 30 | 6.3 | 1.40 | 2.03 | 0.635 | 7.0 | 1500 | 23.1 |
| | | 38 | 7.1 | 1.40 | 2.03 | 0.497 | 7.0 | 1000 | 24.7 |
| | | 50 | 8.2 | 1.40 | 2.03 | 0.386 | 7.0 | 1000 | 26.9 |
| | | 60 | 9.1 | 1.40 | 2.03 | 0.309 | 7.0 | 1000 | 28.7 |
| | | 80 | 10.5 | 1.40 | 2.03 | 0.234 | 7.0 | 1000 | 31.5 |
| | | 100 | 11.9 | 1.40 | 2.03 | 0.184 | 7.0 | 800 | 34.3 |
| | | 125 | 13.2 | 1.65 | 2.03 | 0.147 | 8.0 | 800 | 37.9 |
| | | 150 | 14.7 | 1.65 | 2.03 | 0.120 | 8.0 | 800 | 40.9 |
| | | 200 | 16.6 | 1.65 | 2.79 | 0.0940 | 8.0 | 800 | 46.4 |
| | | 250 | 18.9 | 1.65 | 2.79 | 0.0736 | 8.0 | 600 | 51.0 |
| 325 | 21.3 | 2.03 | 2.79 | 0.0576 | 10.0 | 600 | 57.4 | | |
| 600V 三芯 | 2.0 | 1/1.6 | 1.6 | 0.76 | 1.14 | 9.10 | 3.5 | 2500 | 9.9 |
| | | 1/2.0 | 2.0 | 0.76 | 1.14 | 5.76 | 3.5 | 2000 | 10.8 |
| | | 1/2.6 | 2.6 | 0.76 | 1.14 | 3.42 | 3.5 | 2000 | 12.1 |
| | | 1/3.2 | 3.2 | 1.14 | 1.52 | 2.25 | 5.5 | 2000 | 16.1 |
| | | 7/0.6 | 1.8 | 0.76 | 1.14 | 9.42 | 3.5 | 2500 | 10.4 |
| | | 7/0.8 | 2.4 | 0.76 | 1.14 | 5.30 | 3.5 | 2000 | 11.6 |
| | | 7/1.0 | 3.0 | 0.76 | 1.14 | 3.40 | 3.5 | 2000 | 12.9 |
| | | 8 | 7/1.2 | 3.6 | 1.14 | 2.36 | 5.5 | 1500 | 17.0 |
| | 圓形 壓縮 | 14 | 4.4 | 1.14 | 1.52 | 1.33 | 5.5 | 1500 | 18.5 |
| | | 22 | 5.5 | 1.14 | 2.03 | 0.840 | 5.5 | 1500 | 22.0 |
| | | 30 | 6.3 | 1.40 | 2.03 | 0.635 | 7.0 | 1500 | 25.0 |
| | | 38 | 7.1 | 1.40 | 2.03 | 0.497 | 7.0 | 1000 | 27.0 |
| | | 50 | 8.2 | 1.40 | 2.03 | 0.386 | 7.0 | 1000 | 29.0 |
| | | 60 | 9.1 | 1.40 | 2.03 | 0.309 | 7.0 | 1000 | 31.0 |
| | | 80 | 10.5 | 1.40 | 2.03 | 0.234 | 7.0 | 1000 | 34.0 |
| | | 100 | 11.9 | 1.40 | 2.03 | 0.184 | 7.0 | 800 | 37.0 |
| | | 125 | 13.2 | 1.65 | 2.03 | 0.147 | 8.0 | 800 | 41.0 |
| | | 150 | 14.7 | 1.65 | 2.79 | 0.120 | 8.0 | 800 | 46.0 |
| | | 200 | 16.6 | 1.65 | 2.79 | 0.0940 | 8.0 | 800 | 50.0 |
| | | 250 | 18.9 | 1.65 | 2.79 | 0.0736 | 8.0 | 600 | 55.0 |
| 325 | 21.3 | 2.03 | 2.79 | 0.0576 | 10.0 | 600 | 62.0 | | |

| | 導體 | | | 絕緣厚度 | 被覆厚度 | 最大 導體電阻 (20℃) | 試驗電壓 kV | 最小 絕緣電阻 (20℃) MΩ-km | 完成外徑 (約) mm |
|-------------|-----------------|-------|-----------|--------|--------|---------------------|------------|------------------------------|-------------------|
| | 標稱 截面 | 構成 | 外徑 (約) | | | | | | |
| | mm ² | No/mm | mm | | | | | | |
| 600V 四芯 | 2.0 | 1/1.6 | 1.6 | 0.76 | 1.14 | 9.10 | 3.5 | 2500 | 10.7 |
| | | 1/2.0 | 2.0 | 0.76 | 1.14 | 5.76 | 3.5 | 2000 | 11.7 |
| | | 1/2.6 | 2.6 | 0.76 | 1.14 | 3.42 | 3.5 | 2000 | 13.1 |
| | | 1/3.2 | 3.2 | 1.14 | 1.52 | 2.25 | 5.5 | 2000 | 16.8 |
| | | 7/0.6 | 1.8 | 0.76 | 1.14 | 9.42 | 3.5 | 2500 | 11.2 |
| | | 7/0.8 | 2.4 | 0.76 | 1.14 | 5.30 | 3.5 | 2000 | 12.7 |
| | | 7/1.0 | 3.0 | 0.76 | 1.52 | 3.40 | 3.5 | 2000 | 14.9 |
| | | 8 | 7/1.2 | 3.6 | 1.14 | 2.36 | 5.5 | 1500 | 18.5 |
| | 圓形 壓縮 | 14 | 4.4 | 1.14 | 1.52 | 1.33 | 5.5 | 1500 | 21.0 |
| | | 22 | 5.5 | 1.14 | 2.03 | 0.840 | 5.5 | 1500 | 24.0 |
| | | 30 | 6.3 | 1.40 | 2.03 | 0.635 | 7.0 | 1500 | 27.0 |
| | | 38 | 7.1 | 1.40 | 2.03 | 0.497 | 7.0 | 1000 | 29.0 |
| | | 50 | 8.2 | 1.40 | 2.03 | 0.386 | 7.0 | 1000 | 32.0 |
| | | 60 | 9.1 | 1.40 | 2.03 | 0.309 | 7.0 | 1000 | 34.0 |
| | | 80 | 10.5 | 1.40 | 2.03 | 0.234 | 7.0 | 1000 | 38.0 |
| | | 100 | 11.9 | 1.40 | 2.03 | 0.184 | 7.0 | 800 | 43.0 |
| | | 125 | 13.2 | 1.65 | 2.03 | 0.147 | 8.0 | 800 | 47.0 |
| | | 150 | 14.7 | 1.65 | 2.79 | 0.120 | 8.0 | 800 | 51.0 |
| | | 200 | 16.6 | 1.65 | 2.79 | 0.0940 | 8.0 | 800 | 55.0 |
| | | 250 | 18.9 | 1.65 | 2.79 | 0.0736 | 8.0 | 600 | 60.0 |
| 325 | 21.3 | 2.03 | 3.56 | 0.0576 | 10.0 | 600 | 70.0 | | |
| 2000V 單芯 | 2.0 | 7/0.6 | 1.8 | 1.14 | 0.38 | 9.24 | 5.5 | 3500 | 7.3 |
| | 3.5 | 7/0.8 | 2.4 | 1.14 | 0.38 | 5.20 | 5.5 | 3000 | 7.9 |
| | 5.5 | 7/1.0 | 3.0 | 1.14 | 0.38 | 3.33 | 5.5 | 2500 | 8.4 |
| | 8 | 7/1.2 | 3.6 | 1.40 | 0.38 | 2.31 | 7.0 | 2500 | 9.6 |
| | 圓形 壓縮 | 14 | 4.4 | 1.40 | 0.76 | 1.30 | 7.0 | 2000 | 11.6 |
| | | 22 | 5.5 | 1.40 | 0.76 | 0.824 | 7.0 | 2000 | 12.8 |
| | | 30 | 6.3 | 1.65 | 0.76 | 0.623 | 7.0 | 2000 | 13.8 |
| | | 38 | 7.1 | 1.65 | 0.76 | 0.487 | 8.0 | 1500 | 14.6 |
| | | 50 | 8.2 | 1.65 | 1.14 | 0.378 | 8.0 | 1500 | 16.4 |
| | | 60 | 9.1 | 1.65 | 1.14 | 0.303 | 8.0 | 1500 | 17.3 |
| | | 80 | 10.5 | 1.65 | 1.14 | 0.229 | 8.0 | 1500 | 18.7 |
| | | 100 | 11.9 | 1.65 | 1.14 | 0.180 | 8.0 | 1000 | 20.0 |
| 125 | | 13.2 | 1.90 | 1.65 | 0.144 | 9.5 | 1000 | 22.0 | |
| 150 | | 14.7 | 1.90 | 1.65 | 0.118 | 9.5 | 1000 | 24.0 | |
| 200 | | 16.6 | 1.90 | 1.65 | 0.0922 | 9.5 | 800 | 26.0 | |
| 250 | | 18.9 | 1.90 | 1.65 | 0.0722 | 9.5 | 800 | 28.0 | |
| 325 | 21.3 | 2.29 | 1.65 | 0.0565 | 11.5 | 800 | 32.0 | | |
| 400 | 24.1 | 2.29 | 1.65 | 0.0454 | 11.5 | 800 | 33.0 | | |
| 500 | 26.9 | 2.29 | 1.65 | 0.0373 | 11.5 | 600 | 35.0 | | |
| 2000V 三芯 | 2.0 | 7/0.6 | 1.8 | 1.14 | 1.14 | 9.42 | 5.5 | 3500 | 13.8 |
| | 3.5 | 7/0.8 | 2.4 | 1.14 | 1.14 | 5.30 | 5.5 | 3000 | 15.0 |
| | 5.5 | 7/1.0 | 3.0 | 1.14 | 1.52 | 3.40 | 5.5 | 2500 | 18.0 |
| | 8 | 7/1.2 | 3.6 | 1.40 | 1.52 | 2.36 | 7.0 | 2500 | 21.0 |
| | 圓形 壓縮 | 14 | 4.4 | 1.40 | 1.52 | 1.33 | 7.0 | 2000 | 23.0 |
| | | 22 | 5.5 | 1.40 | 2.03 | 0.840 | 7.0 | 2000 | 28.0 |
| | | 30 | 6.3 | 1.65 | 2.03 | 0.635 | 7.0 | 2000 | 29.0 |
| | | 38 | 7.1 | 1.65 | 2.03 | 0.497 | 8.0 | 1500 | 31.0 |
| | | 50 | 8.2 | 1.65 | 2.03 | 0.386 | 8.0 | 1500 | 34.0 |
| | | 60 | 9.1 | 1.65 | 2.03 | 0.309 | 8.0 | 1500 | 35.0 |
| | | 80 | 10.5 | 1.65 | 2.03 | 0.234 | 8.0 | 1500 | 38.0 |
| | | 100 | 11.9 | 1.65 | 2.03 | 0.184 | 8.0 | 1000 | 41.0 |
| 125 | | 13.2 | 1.90 | 2.79 | 0.147 | 9.5 | 1000 | 46.0 | |
| 150 | | 14.7 | 1.90 | 2.79 | 0.120 | 9.5 | 1000 | 50.0 | |
| 200 | | 16.6 | 1.90 | 2.79 | 0.0940 | 9.5 | 800 | 54.0 | |
| 250 | | 18.9 | 1.90 | 2.79 | 0.0736 | 9.5 | 800 | 59.0 | |
| 325 | 21.3 | 2.29 | 2.79 | 0.0576 | 11.5 | 800 | 68.0 | | |

* 版權屬於華新麗華股份有限公司所有，非經授權不得擅自修改或複製。



總公司：台北市信義區松智路1號25樓
 新莊廠：台北縣新莊市新樹路397號

TEL：(02) 87262211 FAX：(02) 27202234
 業務專線 TEL：(02) 22029121 FAX：(02) 22025166
 (02) 22025155

XLPE-PVC 電力電纜

| | 導體 | | | 絕緣厚度 | 被覆厚度 | 最大 導體電阻 (20℃) | 試驗電壓 | 最小 絕緣電阻 (20℃) | 完成外徑 (約) | |
|--|--|-------|-----------|--------|--------|---------------------|------|---------------------|-------------|------|
| | 標稱 截面積 | 構成 | 外徑 (約) | | | | | | | |
| | mm ² | No/mm | mm | | | | | | | |
| 5000V 單芯 | 8 | 7/1.2 | 3.6 | 2.29 | 1.14 | 2.31 | 18 | 3000 | 14.0 | |
| | 14 | 圓 | 4.4 | 2.29 | 1.52 | 1.30 | 18 | 3000 | 16.0 | |
| | 22 | | 5.5 | 2.29 | 1.52 | 0.824 | 18 | 2500 | 17.5 | |
| | 30 | | 6.3 | 2.29 | 1.52 | 0.623 | 18 | 2500 | 18.5 | |
| | 38 | | 7.1 | 2.29 | 1.52 | 0.487 | 18 | 2000 | 19.0 | |
| | 50 | 形 | 8.2 | 2.29 | 1.52 | 0.378 | 18 | 2000 | 20.0 | |
| | 60 | | 9.1 | 2.29 | 1.52 | 0.303 | 18 | 2000 | 21.0 | |
| | 80 | 壓 | 10.5 | 2.29 | 2.03 | 0.229 | 18 | 2000 | 23.5 | |
| | 100 | | 11.9 | 2.29 | 2.03 | 0.180 | 18 | 1500 | 25.0 | |
| | 125 | | 13.2 | 2.29 | 2.03 | 0.144 | 18 | 1500 | 26.5 | |
| | 150 | | 14.7 | 2.29 | 2.03 | 0.118 | 18 | 1500 | 28.5 | |
| | 200 | 縮 | 16.6 | 2.29 | 2.03 | 0.0922 | 18 | 1000 | 30.5 | |
| | 250 | | 18.9 | 2.29 | 2.03 | 0.0722 | 18 | 1000 | 33.5 | |
| | 325 | | 21.3 | 2.29 | 2.03 | 0.0565 | 18 | 1000 | 36.0 | |
| | 400 | | 24.1 | 2.29 | 2.03 | 0.0454 | 18 | 800 | 39.0 | |
| | 500 | 26.9 | 2.29 | 2.03 | 0.0373 | 18 | 800 | 41.5 | | |
| 5000V 三芯 | 8 | 7/1.2 | 3.6 | 2.29 | 2.03 | 2.36 | 18 | 3000 | 29.0 | |
| | 14 | 圓 | 4.4 | 2.29 | 2.03 | 1.33 | 18 | 3000 | 32.0 | |
| | 22 | | 5.5 | 2.29 | 2.03 | 0.840 | 18 | 2500 | 34.0 | |
| | 30 | | 6.3 | 2.29 | 2.03 | 0.635 | 18 | 2000 | 35.5 | |
| | 38 | | 7.1 | 2.29 | 2.03 | 0.497 | 18 | 2000 | 38.0 | |
| | 50 | 形 | 8.2 | 2.29 | 2.03 | 0.386 | 18 | 2000 | 40.0 | |
| | 60 | | 9.1 | 2.29 | 2.03 | 0.309 | 18 | 2000 | 42.5 | |
| | 80 | 壓 | 10.5 | 2.29 | 2.03 | 0.234 | 18 | 2000 | 44.5 | |
| | 100 | | 11.9 | 2.29 | 2.79 | 0.184 | 18 | 1500 | 50.5 | |
| | 125 | | 13.2 | 2.29 | 2.79 | 0.147 | 18 | 1500 | 53.0 | |
| | 150 | | 14.7 | 2.29 | 2.79 | 0.120 | 18 | 1500 | 57.5 | |
| | 200 | 縮 | 16.6 | 2.29 | 2.79 | 0.0940 | 18 | 1000 | 62.0 | |
| | 250 | | 18.9 | 2.29 | 2.79 | 0.0736 | 18 | 1000 | 68.0 | |
| | 325 | | 21.3 | 2.29 | 3.56 | 0.0576 | 18 | 1000 | 76.0 | |
| | 8000V 中性點 接地 系統 100% 單芯 | | 14 | 圓 | 4.4 | 2.92 | 1.52 | 1.30 | 23 | 3500 |
| | 22 | 5.5 | 2.92 | | 1.52 | 0.824 | 23 | 3000 | 18.5 | |
| 30 | 6.3 | 2.92 | 1.52 | | 0.623 | 23 | 3000 | 20.0 | | |
| 38 | 7.1 | 2.92 | 2.03 | | 0.487 | 23 | 2500 | 20.5 | | |
| 50 | 形 | 8.2 | 2.92 | 2.03 | 0.378 | 23 | 2500 | 22.5 | | |
| 60 | | 9.1 | 2.92 | 2.03 | 0.303 | 23 | 2000 | 23.5 | | |
| 80 | 壓 | 10.5 | 2.92 | 2.03 | 0.229 | 23 | 2000 | 25.0 | | |
| 100 | | 11.9 | 2.92 | 2.03 | 0.180 | 23 | 2000 | 26.0 | | |
| 125 | | 13.2 | 2.92 | 2.03 | 0.144 | 23 | 2000 | 26.5 | | |
| 150 | | 14.7 | 2.92 | 2.03 | 0.118 | 23 | 1500 | 29.0 | | |
| 200 | 縮 | 16.6 | 2.92 | 2.03 | 0.0922 | 23 | 1500 | 31.0 | | |
| 250 | | 18.9 | 2.92 | 2.03 | 0.0722 | 23 | 1500 | 33.5 | | |
| 325 | | 21.3 | 2.92 | 2.03 | 0.0565 | 23 | 1500 | 37.0 | | |
| 400 | | 24.1 | 2.92 | 2.03 | 0.0454 | 23 | 1500 | 40.0 | | |
| 500 | 26.9 | 2.92 | 2.03 | 0.0373 | 23 | 1000 | 42.5 | | | |
| 8000V 中性點 接地 系統 100% 三芯 | 14 | 圓 | 4.4 | 2.92 | 2.03 | 1.33 | 23 | 3500 | 34.5 | |
| | 22 | | 5.5 | 2.92 | 2.03 | 0.840 | 23 | 3000 | 37.0 | |
| | 30 | | 6.3 | 2.92 | 2.03 | 0.635 | 23 | 2500 | 37.5 | |
| | 38 | | 7.1 | 2.92 | 2.03 | 0.497 | 23 | 2500 | 41.0 | |
| | 50 | 形 | 8.2 | 2.92 | 2.79 | 0.386 | 23 | 2000 | 44.0 | |
| | 60 | | 9.1 | 2.92 | 2.79 | 0.309 | 23 | 2000 | 47.0 | |
| | 80 | 壓 | 10.5 | 2.92 | 2.79 | 0.234 | 23 | 2000 | 50.0 | |
| | 100 | | 11.9 | 2.92 | 2.79 | 0.184 | 23 | 2000 | 53.5 | |
| | 125 | | 13.2 | 2.92 | 2.79 | 0.147 | 23 | 2000 | 55.5 | |
| | 150 | | 14.7 | 2.92 | 2.79 | 0.120 | 23 | 1500 | 60.5 | |
| | 200 | 縮 | 16.6 | 2.92 | 2.79 | 0.0940 | 23 | 1500 | 65.0 | |
| | 250 | | 18.9 | 2.92 | 2.79 | 0.0736 | 23 | 1000 | 71.0 | |
| | 325 | | 21.3 | 2.92 | 3.56 | 0.0576 | 23 | 1000 | 79.0 | |

| | 導體 | | | 絕緣厚度 | 被覆厚度 | 最大 導體電阻 (20℃) | 試驗電壓 | 最小 絕緣電阻 (20℃) | 完成外徑 (約) | | |
|---|---|-------|-----------|------|--------|---------------------|-------|---------------------|-------------|------|------|
| | 標稱 截面積 | 構成 | 外徑 (約) | | | | | | | | |
| | mm ² | No/mm | mm | | | | | | | | |
| 15000V 中性點 接地 系統 100% 單芯 | 38 | 圓 | 7.1 | 4.45 | 2.03 | 0.487 | 35 | 3500 | 25.0 | | |
| | 50 | | 8.2 | 4.45 | 2.03 | 0.378 | 35 | 3500 | 26.0 | | |
| | 60 | | 9.1 | 4.45 | 2.03 | 0.303 | 35 | 3000 | 27.0 | | |
| | 80 | | 10.5 | 4.45 | 2.03 | 0.229 | 35 | 3000 | 28.0 | | |
| | 100 | 形 | 11.9 | 4.45 | 2.03 | 0.180 | 35 | 2500 | 30.0 | | |
| | 125 | | 13.2 | 4.45 | 2.03 | 0.144 | 35 | 2500 | 31.0 | | |
| | 150 | 壓 | 14.7 | 4.45 | 2.03 | 0.118 | 35 | 2000 | 34.0 | | |
| | 200 | | 16.6 | 4.45 | 2.03 | 0.0922 | 35 | 2000 | 36.0 | | |
| | 250 | | 18.9 | 4.45 | 2.03 | 0.0722 | 35 | 1500 | 38.0 | | |
| | 325 | | 21.3 | 4.45 | 2.03 | 0.0565 | 35 | 1500 | 41.0 | | |
| | 400 | 縮 | 24.1 | 4.45 | 2.03 | 0.0454 | 35 | 1500 | 43.5 | | |
| | 500 | | 26.9 | 4.45 | 2.79 | 0.0373 | 35 | 1500 | 48.5 | | |
| | 15000V 中性點 接地 系統 100% 三芯 | | 38 | 圓 | 7.1 | 4.45 | 2.79 | 0.497 | 35 | 3500 | 49.5 |
| | 50 | | 8.2 | | 4.45 | 2.79 | 0.386 | 35 | 3500 | 52.0 | |
| | 60 | 9.1 | 4.45 | | 2.79 | 0.309 | 35 | 3000 | 54.0 | | |
| | 80 | 10.5 | 4.45 | | 2.79 | 0.234 | 35 | 3000 | 56.0 | | |
| 100 | 形 | 11.9 | 4.45 | 2.79 | 0.184 | 35 | 2500 | 60.5 | | | |
| 125 | | 13.2 | 4.45 | 2.79 | 0.147 | 35 | 2500 | 63.0 | | | |
| 150 | 壓 | 14.7 | 4.45 | 2.79 | 0.120 | 35 | 2000 | 68.5 | | | |
| 200 | | 16.6 | 4.45 | 2.79 | 0.0940 | 35 | 2000 | 73.0 | | | |
| 250 | | 18.9 | 4.45 | 3.56 | 0.0736 | 35 | 1500 | 80.0 | | | |
| 325 | | 21.3 | 4.45 | 3.56 | 0.0576 | 35 | 1500 | 86.0 | | | |
| 25000V 中性點 接地 系統 100% 單芯 | 38 | 圓 | 7.1 | 6.60 | 2.03 | 0.487 | 52 | 3600 | 29.5 | | |
| 50 | 8.2 | | 6.60 | 2.03 | 0.378 | 52 | 3600 | 30.0 | | | |
| 60 | 9.1 | | 6.60 | 2.03 | 0.303 | 52 | 3000 | 32.0 | | | |
| 80 | 10.5 | | 6.60 | 2.03 | 0.229 | 52 | 3000 | 33.0 | | | |
| 100 | 形 | 11.9 | 6.60 | 2.03 | 0.180 | 52 | 2800 | 35.0 | | | |
| 125 | | 13.2 | 6.60 | 2.03 | 0.144 | 52 | 2800 | 36.0 | | | |
| 150 | 壓 | 14.7 | 6.60 | 2.03 | 0.118 | 52 | 2000 | 38.0 | | | |
| 200 | | 16.6 | 6.60 | 2.03 | 0.0922 | 52 | 2000 | 40.0 | | | |
| 250 | | 18.9 | 6.60 | 2.03 | 0.0722 | 52 | 1800 | 42.5 | | | |
| 325 | | 21.3 | 6.60 | 2.79 | 0.0565 | 52 | 1500 | 47.0 | | | |
| 400 | 縮 | 24.1 | 6.60 | 2.79 | 0.0454 | 52 | 1500 | 50.0 | | | |
| 500 | | 26.3 | 6.60 | 2.79 | 0.0373 | 52 | 1500 | 52.0 | | | |
| 25000V 中性點 接地 系統 100% 三芯 | | 38 | 圓 | 7.1 | 6.60 | 2.79 | 0.497 | 52 | 3600 | 59.0 | |
| 50 | | 8.2 | | 6.60 | 2.79 | 0.386 | 52 | 3600 | 61.0 | | |
| 60 | 9.1 | 6.60 | | 2.79 | 0.309 | 52 | 3000 | 64.0 | | | |
| 80 | 10.5 | 6.60 | | 2.79 | 0.234 | 52 | 3000 | 66.0 | | | |
| 100 | 形 | 11.9 | 6.60 | 2.79 | 0.184 | 52 | 2800 | 71.0 | | | |
| 125 | | 13.2 | 6.60 | 3.56 | 0.147 | 52 | 2800 | 74.0 | | | |
| 150 | 壓 | 14.7 | 6.60 | 3.56 | 0.120 | 52 | 2000 | 80.0 | | | |
| 200 | | 16.6 | 6.60 | 3.56 | 0.0940 | 52 | 2000 | 84.0 | | | |
| 250 | | 18.9 | 6.60 | 3.56 | 0.0736 | 52 | 1800 | 89.0 | | | |
| 325 | | 21.3 | 6.60 | 3.56 | 0.0576 | 52 | 1500 | 96.0 | | | |

* 版權屬於華新麗華股份有限公司所有，非經授權不得擅自修改或複製。



總公司：台北市信義區松智路1號25樓
 新莊廠：台北縣新莊市新樹路397號

TEL：(02) 87262211
 業務專線 TEL：(02) 22029121
 (02) 22025155

FAX：(02) 27202234
 FAX：(02) 22025166